

TEX-F.O.D.

Fuel Oil Delivery Hose









Designed for the transfer and delivery of fuels, oils, kerosene, diesel and other petroleum-based products for home, commercial, marine and industrial service. Its braided synthetic reinforcement allows for extreme flexibility, reduced twisting and ease of handling, while maintaining kink resistance. Drivers will prefer this hose because of its static conductive tube, abrasion and oil resistance and 250psi working pressures in all sizes.



TECHNICAL DATA

Tube	Black, NBR (ARPM Class A)
Cover	Red, NBR (ARPM Class A)
Reinforcement	2 braided polyester cords
Safety Factor	4:1
Temperature	-40°F to +180°F
Branding	TEXCEL F.O.D. Fuel Oil Delivery Hose - <ID> - 250PSI WP LOT (white ink letters)

 I.D.	 Part Number*	 O.D.	 Std. Length	 Working Pressure (psi)	 Lbs./Ft.
1"	FOD-16-XXX	1-3 ² / ₆₄ "	100'/125'/150'/175'	250	0.65
1-1/4"	FOD-20-XXX	1-5 ¹ / ₆₄ "	100'/125'/150'/175'	250	0.87
1-3/8"	FOD-22-XXX	1-5 ⁶ / ₆₄ "	100'/125'/150'/175'	250	0.91
1-1/2"	FOD-24-XXX	2-6 ¹ / ₆₄ "	100'/125'/150'/175'	250	1.12
2"	FOD-32-XXX	2-4 ¹ / ₆₄ "	75'/100'	200	1.38

*Replace XXX in Part Number with standard length required