

GAMMA™-TANK-BIO

Biofuel Tank Truck Hose









Suction and discharge hose for transport of biofuel, biodiesel blends, B-100, E-100, ethanol blends and fuel mixtures with aromatic content up to 60%.
Used for tank trucks, storage tanks and loading stations.



TECHNICAL DATA

Tube	Special NBR based Oil Resistant Blend
Cover	Black NBR based smooth oil, abrasion, and ozone resistant
WP	150psi 4:1 safety factor
Temperature	-22°F to 185°F
Reinforcement	High tensile textile cord, dual helix, antistatic wire
Lengths	100'



 I.D.	 Part Number	 O.D.	 Std. Length	 Working Pressure (psi)	 Vacuum (in./HG)	 Bend Radius	 Lbs./Ft.
1"	GTA15S1-BIO-1.0-100	1-27/64"	100'	150	29	4"	0.50
1-1/4"	GTA15S1-BIO-1.25-100	1-47/64"	100'	150	29	5"	0.67
1-1/2"	GTA15S1-BIO-1.5-100	1-62/64"	100'	150	29	6"	0.77
2"	GTA15S1-BIO-2.0-100	2-33/64"	100'	150	29	8"	1.10
2-1/2"	GTA15S1-BIO-2.5-100	3-2/64"	100'	150	29	10"	1.68
3"	GTA15S1-BIO-3.0-100	3-35/64"	100'	150	29	12"	2.10
4"	GTA15S1-BIO-4.0-100	4-42/64"	100'	150	29	16"	3.10